

FEATURES

- ▶ Ultra Compact Size 1.0 x 1.0 x 0.64"
- ▶ Fully Encapsulated Plastic Case for PCB and Chassis Mounting Version
- ▶ Universal Input 85~264VAC
- ▶ Protection Class II as per IEC/EN 60536
- ▶ I/O Isolation 3000VAC with Reinforced Insulation
- ▶ No Min. Load Requirement
- ▶ Operating Ambient Temp. Range -25°C to +70°C
- ▶ Overload/Voltage and Short Circuit Protection
- ▶ Designed-in EMI Emission meets EN55011/32/14-1 Class B & FCC Level B
- ▶ Designed-in EMC Immunity meets EN61000-4-2,3,4,5,6,8,11
- ▶ Eco Design, No Load Input Power 300mW max.
- ▶ Safety Approval to UL/cUL/IEC/EN 60950-1, TUV IEC/EN 60335-1 & CE Marking


PRODUCT OVERVIEW

The new AAF-05 Series from MINMAX is a range of ultra-small, fully encapsulated 5 Watt AC/DC power supply modules. They are designed for easy PCB mounting with solder pins. The modules feature EMI-filter to meet EN 55011/32 and EN 55014-1, class B. EMC immunity complies with EN 61000-6-1. The low stand-by power consumption complies with European ErP Directive 2009/125/EC.

Universal input voltage range of 85-264VAC and an International safety approval package qualifies these power modules for worldwide markets.

The AAF-05 power supplies provide a cost effective solution for space critical applications in consumer appliances and instrumentation and communication equipment.

Model Selection Guide

Model Number	Output Voltage	Output Current		Input Current @Max. Load	Max. Capacitive Load	Efficiency (typ.) @Max. Load
		Max.	Peak ⁽¹⁾			
		VDC	mA	mA	mA(typ.)	μF
AAF-05S03	3.3	1515	1970	117	2200	74
AAF-05S05	5	1000	1300	108	1000	80
AAF-05S09	9	555	721	106	300	82
AAF-05S12	12	416	540	106	160	82
AAF-05S15	15	333	433	104	100	83
AAF-05S24	24	208	270	104	43	83
AAF-05S48	48	104	135	102	10	85

Input Specifications

Parameter	Conditions / Model	Min.	Typ.	Max.	Unit
Input Voltage Range	All Models	85	---	264	VAC
Input Frequency Range		47	---	63	Hz
Input Voltage Range		120	---	370	VDC
No-Load Power Consumption		---	---	300	mW
Inrush Current (Cold Start at 25°C)	115VAC	---	---	20	A
	230VAC	---	---	40	A

Output Specifications

Parameter	Conditions / Model	Min.	Typ.	Max.	Unit	
Output Voltage Accuracy		---	---	±2.0	%Vnom.	
Line Regulation	Vin=Min. to Max. @Full Load	---	---	±1.0	%	
Load Regulation	Io=0% to 100%	---	---	±1.0	%	
Ripple & Noise	0-20 MHz Bandwidth	3.3V & 5VDC Output Models	---	---	60	mV _{PP} of Vo
		Other Output Models	---	---	1	%V _{PP} of Vo
Minimum Load	No minimum Load Requirement					
Over Voltage Protection	Zener Diode Clamp	---	125	190	% of Vo	
Temperature Coefficient		---	---	±0.05	%/°C	
Overshoot		---	---	5	%Vout	
Over Load Protection	Foldback, auto-recovery (long term overload condition may cause damage)	135	150	---	%Inom.	
Short Circuit Protection	Hiccup mode, Automatic Recovery					

General Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	60 Seconds	3000	---	---	VACrms
I/O Isolation Resistance	500 VDC	100	---	---	MΩ
Switching Frequency		---	65	---	KHz
Hold-up Time	115VAC, Full Load	---	8	---	ms
	230VAC, Full Load	---	40	---	ms
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	628,000	---	---	Hours
Protection Class II	According IEC/EN 60536				
Safety Approvals	UL/cUL 60950-1 recognition (UL certificate), IEC/EN 60950-1 (CB-report) IEC/EN 60335-1 recognition (CB-report, TUV certificate)				

EMC Specifications

Parameter	Standards & Level		Performance
EMI	Conduction & Radiation	EN 55011, EN 55014-1, EN 55032, FCC part 15	Class B
EMS	EN 55014-2, EN 55024		
	ESD	EN 61000-4-2 Air ± 8kV, Contact ± 4kV	A
	Radiated immunity	EN 61000-4-3 10V/m	A
	Fast transient	EN 61000-4-4 ±2kV	A
	Surge	EN 61000-4-5 ±1kV	A
	Conducted immunity	EN 61000-4-6 10Vrms	A
	PFMF	EN 61000-4-8 30A/m	A
	Dips	EN 61000-4-11 30% 10ms	A
Interruptions	EN 61000-4-11 >95% 5000ms	B	


Environmental Specifications

Parameter	Conditions	Min.	Max.	Unit
Operating Ambient Temperature Range	Natural Convection	-25	+70	°C
Storage Temperature Range		-40	+85	°C
Power Derating	+50°C to +70°C	0.125		W / °C
Humidity (non condensing)		---	95	% rel. H
Cooling	Natural Convection			
Lead Temperature (1.5mm from case for 10Sec.)		---	260	°C

Notes

- Peak load lasting <30s with a maximum duty cycle of 10%, average output power not to exceed maximum power.
- All specifications typical at Ta=+25°C, resistive load, 115VAC, 60Hz input voltage and after warm-up time rated output current unless otherwise noted.
- Ripple & Noise of PCB mounting type measured with a 1μF/50V MLCC.
- We recommend to protect the converter by a slow blow fuse in the input supply line.
- Other input and output voltage may be available, please contact factory.
- That "natural convection" is about 20LFM but is not equal to still air (0 LFM).
- Specifications are subject to change without notice.

Package Specifications PCB Mounting



Pin Connections

Pin	Function
1	AC (N)
2	AC (L)
3	NC
4	-Vout
5	+Vout


NC: No Connection

- ▶ All dimensions in mm (inches)
- ▶ Tolerance: ± 0.5 (± 0.01)
- ▶ Pin diameter $\varnothing 0.6 \pm 0.1$ (0.02 ± 0.004)

Physical Characteristics

Case Size	: 25.4x25.4x16.3mm (1.0x1.0x0.64 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Tinned Copper
Weight	: 19.7g

Package Specifications Chassis Mounting



Connections

Pin	Function
1	AC (N)
2	AC (L)
3	NC
4	-Vout
5	+Vout

- ▶ All dimensions in mm (inches)
- ▶ Tolerance: ± 0.5 (± 0.02)

Physical Characteristics

Case Size	: 42.0x26.0x19.3mm (1.65x1.02x0.76 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Weight	: 23.9g

Order Code Table	
PCB Mounting	Chassis Mounting
AAF-05S03	AAF-05S03C
AAF-05S05	AAF-05S05C
AAF-05S09	AAF-05S09C
AAF-05S12	AAF-05S12C
AAF-05S15	AAF-05S15C
AAF-05S24	AAF-05S24C
AAF-05S48	AAF-05S48C